

	DS-	B1- MB- (for modular)	1 Style	2 Indicator	1 Contacts	
GAGE SIZE	INDICATOR GRADUATION	HIGH AMPLIFICATION INDICATOR	PART NUMBER	TRADITIONAL INDICATOR	TRADITIONAL PART NUMBER	
.63" - 1.00"	.0005 <sup>s</sup>	DS-214-005	DS-B1-10101			
	.0001 <sup>s</sup>	DS-219-01	DS-B1-11101			
	.0001"	DS-2150-01	DS-B1-12101			
	.00025"	DS-21100-025	DS-B1-10111			
	.0005"	DS-21100-05	DS-B1-14101			
	NONE	LESS INDICATING UNIT	DS-B1-15101			
	0.005mm	DS-2125-005mm	DS-B1-17101			
	0.002mm	DS-2110-002mm	DS-B1-18101			
	0.002mm <sup>s</sup>	DS-2102-002mm	DS-B1-19101			
	0.001mm <sup>s</sup>	DS-2101-001mm	DS-B1-10121			
16 - 25.4mm	.0001" / .002mm <sup>s</sup>	S2LM	DS-B1-12101M			
	.00005" / 0.001mm	DIGITAL	DS-B5-10101			
	1.00 - 1.53"	.0005 <sup>s</sup>	DS-214-005	DS-B1-10102		
		.0001 <sup>s</sup>	DS-219-01	DS-B1-11102		
		.0001"	DS-2150-01	DS-B1-12102	DS-2DM025-01	DS-B2-12102
		.00025"	DS-21100-025	DS-B1-10112		
		.0005"	DS-21100-05	DS-B1-14102	DS-2DM050-05	DS-B2-14102
		NONE	LESS INDICATING UNIT	DS-B1-15102		
		0.005mm	DS-2125-005mm	DS-B1-17102	DS-2DM012-005mm	DS-B2-17102
		0.002mm	DS-2110-002mm	DS-B1-18102	DS-2DM005-002mm	DS-B2-18102
0.002mm <sup>s</sup>		DS-2102-002mm	DS-B1-19102			
0.001mm <sup>s</sup>		DS-2101-001mm	DS-B1-10122			
25.4 - 38.9mm	.0001" / .002mm <sup>s</sup>	S2LM	DS-B1-12102M			
	.00005" / 0.001mm	DIGITAL	DS-B5-10102			

	0 Indicator	4 Gage Size	-12 A Length			
GAGE SIZE	INDICATOR GRADUATION	HIGH AMPLIFICATION INDICATOR	PART NUMBER	TRADITIONAL INDICATOR	TRADITIONAL PART NUMBER	
1.50 - 2.16"	.0005 <sup>s</sup>	DS-214-005	DS-B1-10103			
	.0001 <sup>s</sup>	DS-219-01	DS-B1-11103			
	.0001"	DS-2150-01	DS-B1-12103	DS-2DM025-01	DS-B2-12103	
	.00025"	DS-21100-025	DS-B1-10113			
	.0005"	DS-21100-05	DS-B1-14103	DS-2DM050-05	DS-B2-14103	
	NONE	LESS INDICATING UNIT	DS-B1-15103			
	0.005mm	DS-2125-005mm	DS-B1-17103	DS-2DM012-005mm	DS-B2-17103	
	0.002mm	DS-2110-002mm	DS-B1-18103	DS-2DM005-002mm	DS-B2-18103	
	0.002mm <sup>s</sup>	DS-2102-002mm	DS-B1-19103			
	0.001mm <sup>s</sup>	DS-2101-001mm	DS-B1-10123			
38.1 - 54.8mm	.0001" / .002mm <sup>s</sup>	S2LM	DS-B1-12103M			
	.00005" / 0.001mm	DIGITAL	DS-B5-10103			
	2.12 - 3.13"	.0005 <sup>s</sup>	DS-214-005	DS-B1-10104		
		.0001 <sup>s</sup>	DS-219-01	DS-B1-11104		
		.0001"	DS-2150-01	DS-B1-12104	DS-2DM025-01	DS-B2-12104
		.00025"	DS-21100-025	DS-B1-10114		
		.0005"	DS-21100-05	DS-B1-14104	DS-2DM050-05	DS-B2-14104
		NONE	LESS INDICATING UNIT	DS-B1-15104		
		0.005mm	DS-2125-005mm	DS-B1-17104	DS-2DM012-005mm	DS-B2-17104
		0.002mm	DS-2110-002mm	DS-B1-18104	DS-2DM005-002mm	DS-B2-18104
0.002mm <sup>s</sup>		DS-2102-002mm	DS-B1-19104			
0.001mm <sup>s</sup>		DS-2101-001mm	DS-B1-10124			
54.0 - 79.5mm	.0001" / .002mm <sup>s</sup>	S2LM	DS-B1-12104M			
	.00005" / 0.001mm	DIGITAL	DS-B5-10104			
	3.09 - 6.13"	.0005 <sup>s</sup>	DS-214-005	DS-B1-10105		
		.0001 <sup>s</sup>	DS-219-01	DS-B1-11105		
		.0001"	DS-2150-01	DS-B1-12105	DS-2DM025-01	DS-B2-12105
		.00025"	DS-21100-025	DS-B1-10115		
		.0005"	DS-21100-05	DS-B1-14105	DS-2DM050-05	DS-B2-14105
		NONE	LESS INDICATING UNIT	DS-B1-15105		
		0.005mm	DS-2125-005mm	DS-B1-17105	DS-2DM012-005mm	DS-B2-17105
		0.002mm	DS-2110-002mm	DS-B1-18105	DS-2DM005-002mm	DS-B2-18105
0.002mm <sup>s</sup>		DS-2102-002mm	DS-B1-19105			
0.001mm <sup>s</sup>		DS-2101-001mm	DS-B1-10125			
78.5 - 156mm	.0001" / .002mm <sup>s</sup>	S2LM	DS-B1-12105M			
	.00005" / 0.001mm	DIGITAL	DS-B5-10105			

<sup>s</sup> = single revolution indicator.

## OPTIONAL CONTACT POINTS

OPTION	1	2	4	5	7	8
Gaging Contact	Steel	Carbide	Diamond	Carbide	Diamond	Offset Contact Configuration
Centralizing Contact	Steel	Steel	Steel	Carbide	Carbide	H Dimension